

SPECIFICATIONS



Model	Dimensions	COM Yards
LB-1	Seat Height 18"	Total Yards 3.65
Weight	Seat Width 24"	Seat Yards 1.5
76 lbs	Overall Height 32"	Back Yards 2.15
	Depth 28"	

*Intended for indoor use only

Stinson
SEE / SAMPLE / SPEC



DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Upholstery: Seats and backs are available in different fabrics. Available in California TB133 compliant upholstery.

Upholstery

View our upholstery selections at www.norix.com/fabrics. Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

Assembly

None required

Fabrication & Material

Frame: The Harmony® Series is built around a robust fully welded steel frame for maximum strength and durability.

Cushions: Polyurethane foam is glued to high strength plywood and connected to a tamper proof steel frame. 2.7 pound high density polyurethane foam in both the seat and back provides longevity and support in high traffic applications. Upholstery is available in a wide selection of fabrics while steel plate encloses the bottom and tamper-resistant fasteners provide reinforced security.

Feet: Injection-molded nylon feet are engineered for strength and to protect floors. Made in the U.S.A.

Installation

None required

Warranty

5 year limited replacement warranty; lifetime structural warranty on internal steel frame. Refer to Norix® Terms and Conditions for details.

Maintenance

Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

TESTING

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.
- Compliant with Healthier Hospitals guidelines

Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,000 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")