

## SPECIFICATIONS



### Model

EE

### Weight

215 lbs

\*Intended for indoor use only

### Dimensions

Seat Height	18"
Seat Width	69"
Overall Height	32.5"
Depth	29"
Width	75"
Arm Height	26.4"

### COM Yards

Total Yards	14.5
Seat Yards	4.2
Back Yards	6.75
Arm Yards	3.55

**Stinson**  
SEE / SAMPLE / SPEC



## DETAILS

### Finishes

See Design Guide for finish options.

\*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

### Upholstery

View our upholstery selections at [www.norix.com/fabrics](http://www.norix.com/fabrics). Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM.

### Options

Available in California TB133 compliant upholstery

### Assembly

None required

### Fabrication & Material

**Frame:** The Element Series features a durable wood frame with steel-to-steel connections for strong and robust finish.

**Cushions:** Constructed of a 2.7 lb flexible polyurethane foam wrapped in fabric for comfort, ideal for high traffic areas and suitable for health care applications.

**Arm Panel:** Urethane arm caps extend over top surface, are pick and pry resistant and secured with a steel-to-steel connection.

### Installation

None required

### Warranty

10 year limited replacement warranty

### Maintenance

Arm caps are easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

## TESTING

### Environmental Test Standards

- GREENGUARD Certified by UL Environment. Product certified for low chemical emissions to UL 2818. [UL.COM/GG](http://UL.COM/GG).
- Compliant with Healthier Hospitals guidelines

### Performance Test Standards

- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- Meets or exceeds the requirements of ANSI/BIFMA X5.4-2012
- Tested to 1,500 lb static load
- Product dynamic drop tested to a relative impact force of two times BIFMA 5.4 15.4.2 (250 lbs from 18")