SPECIFICATIONS



NORIX

Dimensions		COM Yards
Width	36.3″	Total Yards
Depth	18.3″	
Height	18″	

*Intended for indoor use only

Model MU965

Weight 37 lbs

DETAILS

Finishes

See Design Guide for finish options.

*Due to differences in monitors, printers and materials, actual product colors may vary. Color chips are available for more accurate depiction of color.

Options

Upholstery upgradeable to TB133.

Factory Ballasting (35 lbs).

*Ballastable up to 50 pounds of dry sand or gravel. On site ballast materials not supplied by Norix.

Upholstery

View our upholstery selections at <u>www.norix.</u> <u>com/fabrics</u>. Fabric Grade Levels: Grade B, Grade C, Grade D, Grade E, Grade F, Grade G, Grade H, COM. Upholstery flammability standard upgradable to TB133.

Assembly

None required

Patents

Patents Pending

Fabrication & Material

<u>Base:</u> Strong, one-piece rotationally-molded polyethylene with lightly textured surface allows for easy cleaning.

<u>Inside:</u> High-density flexible foam core designed to withstand high-traffic environments.

Installation

None required

Warranty

10 year limited replacement warranty

Maintenance

Easily cleaned with a damp cloth and a mild soap solution. Refer to upholstery manufacturer's cleaning instructions for specific fabrics.

TESTING

Performance Test Standards Product tested to 500 lbs static load Environmental Test Standards

• GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

• Compliant with Healthier Hospitals guidelines

Flammability Test Standards

Compliant with the following flammability standards: State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies





3.03